Honda Research Institute EU
Honda Research Institute Europe GmbH
https://www.honda-ri.de/

A Hybrid Local Search Framework for the Dynamic Capacitated Arc Routing Problem

Hao Tong, Leandro L. Minku, Stefan Menzel, Bernhard Sendhoff, Xin Yao

2021

Preprint:

Copyright ACM 2021. This is the author's version of the work. It is posted here for your personal use. Not for redistribution. The definitive Version of Record was published in Genetic and Evolutionary Computation Conference Companion (GECCO Companion), https://doi.org/10.1145/3449726.3459450.

A Hybrid Local Search Framework for the Dynamic Capacitated Arc Routing Problem

Hao Tong
Leandro L. Minku
School of Computer Science,
University of Birmingham
Birmingham, UK
{hxt922,L.L.Minku}@cs.bham.ac.uk

Stefan Menzel
Bernhard Sendhoff
Honda Research Institute Europe
Offenbach, Germany
{stefan.menzel,bs}@honda-ri.de

Xin Yao*
School of Computer Science,
University of Birmingham, UK
Department of Computer Science and
Engineering, SUSTech, China
xiny@sustech.edu.cn

ABSTRACT

The static capacitated arc routing problem (CARP) is a challenging combinatorial problem, where vehicles need to be scheduled efficiently for serving a set of tasks with minimal travelling costs. Dynamic CARP (DCARP) considers the occurence of dynamic events during the service process, e.g. traffic congestion, which reduce the quality of the currently applied schedule. Existing research mainly focused on scenarios with large changes but neglected the time limitations of the rescheduling process. In this paper, we investigate DCARP scenarios with small dynamic changes in which events only affect the properties of a few edges. We propose an efficient hybrid local search framework (HyLS) to reschedule the service plan in a short time for a DCARP instance. HyLS maintains an archive that enables it to cover more search areas than single local search algorithms, while its local search mechanisms enable it to find better solutions than meta-heuristic re-optimisation from scratch when restricted to a tight time budget. Our experiments demonstrate HyLS' effectiveness compared to existing local search strategies and meta-heuristic re-optimisation from scratch.

KEYWORDS

Dynamic capacitated arc routing problem, Hybrid local search.

ACM Reference Format:
Hao Tong, Leandro L. Minku, Stefan Menzel, Bernhard Sendhoff, and Xin Yao. 2021. A Hybrid Local Search Framework for the Dynamic Capacitated Arc Routing Problem. In *2021 Genetic and Evolutionary Computation Conference Companion (GECCO '21 Companion), July 10–14, 2021, Lille, France.* ACM, New York, NY, USA, 2 pages. https://doi.org/10.1145/3449726.3459450

1 INTRODUCTION

The capacitated arc routing problem (CARP) is abstracted from a range of real world applications, e.g. mail delivery. Algorithms for solving CARP target to schedule vehicles with limited capacities for serving a set of tasks in a map with minimal travelling costs. However, dynamic events are common in real world applications and consequently affect the executed CARP solution's quality in practice. Therefore, solutions need to be rescheduled frequently and within a tight time budget. Existing research on Dynamic CARP (DCARP) is limited and mainly focused on dynamic scenarios where several larger changes occur on the map, drastically influencing the problem's condition [1]. Usually, a time-consuming strategy has been applied for these scenarios, utilizing meta-heuristic algorithms for re-optimising the new DCARP instance from scratch [4],[7]. One complete optimisation on a small test graph would consume hundreds of seconds as shown in [5]. Dynamic capacitated vehicle routing problem (DCVRP) is a related area that might offer alternatives, but the possible transformation from CVRP to CARP increases the problem's dimension, discouraging attempts to use capacitated VRP algorithms to solve CARP. Therefore, in this paper:

- we propose a novel hybrid local search framework for DCARP (HyLS) which is able to reschedule solutions in a very short time in response to small dynamic changes;
- we demonstrate the efficiency of the proposed HyLS by evaluating our framework against existing meta-heuristics and local search strategies, showing its effectiveness.

This is the author's version of the work. It is posted here for your personal use. Not for redistribution. The definitive Version of Record was published in GECCO '21: Proceedings of the Genetic and Evolutionary Computation Conference Companion, Lille, France, pps. 1344-1345, 10.-14. July 2021, https://doi.org/10.1145/3449726.3459450.

2 HYBRID LOCAL SEARCH FRAMEWORK

Our proposed HyLS framework (Algorithm 1) can find an improved solution for DCARP with a fast response time by removing the crossover operators existing in meta-heuristic algorithms and promoting the neighbourhood of the current solutions. It adopts three effective strategies as follows. The *parallel neighbourhood moves strategy* allows for an efficient use of multiple parallel processes where each slave process computes one neighbourhood move on one solution independently. Five neighbourhood moves (Single Insertion, Double Insertion, Swap, Reverse and Cross [2]) are adopted. The master process collects the improved solutions potentially leading to the optimal solution and maintains an archive to store them (*archive strategy*). For each solution in the archive, the *exhaustive one-step move strategy* is utilized, which optimises a solution until no further neighborhood move improves the solution quality, to find the best neighbour for the solution, thus focusing on the local area. The framework terminates once the optimisation exceeds the time limitation or all solutions in the archive have been optimised.

3 EXPERIMENTS AND ANALYSIS

We compare HyLS with re-optimisation from scratch and other 3 local search algorithms in terms of final solution quality and algorithm efficiency on 72 DCARP instances (3 for each map), which

Algorithm 1: The hybrid local search framework

Input: The updated graph data; Stop locations of outside vehicles; Remaining capacities of outside vehicles;

```
Re-construct the solution S_0 with explicit routes;
Initialize the solution archive (set) SA = {S_0};
Set global best solution S_gb ← S_0;
for each solution S_i in SA do
    Local best solution S_lb ← S_i;
    while true do
        // Parallel for loop
        for each neighborhood move Move_j do
            Solution S_mj = OneStepMove_j(S_lb);
            if improve and archive is not full then
                SA ← SA ∪ S_mj;
        Update local best solution S_lb based on S_mj;
        if not improve or exceed time limitation then
            break;
    if S_lb.cost < S_gb.cost then
        S_gb ← S_lb;
    if exceed time limitation then
        break;
```

Output: The global best solution S_{gb}

are generated from the static CARP dataset *egl* [3] using the DCARP simulator from [7]. The time budget (i.e. termination criterion) for each algorithm in each experiment was set to 5 seconds. All algorithms were implemented in C and run on an Intel Core i7-8700 3.2GHZ.

For each experiment, we present a representative subset of our results in Tables 1 and 2 due to the page limit. Specifically, we highlight our results achieved with the instances from map S4 - C (best result of each instance in grey). We also provide the average ranking, p-value of the Friedman test, and the critical difference (CD) of the Nemenyi test with a level of significance of 0.05 across all 72 DCARP instances for each experiment.

Is HyLS more efficient than re-optimisation strategy? Two powerful meta-heuristic algorithms (MAENS [6] and MASDC [4]) using the re-optimization strategy have been applied and compared with our HyLS in the first experiment (Table 1). HyLS performed better than the other two algorithms on all DCARP instances, because the re-optimisation strategy is too complex to converge within a tight time budget. The provided maximum time limits the number of iterations of the meta-heuristic algorithms, preventing them from finding high-quality solutions when starting from scratch.

***Does HyLS improve the efficiency* of local search?** We compare HyLS with the local search strategy by sequentially using neighbourhood moves (SEQ) [2], SEQ with Iterative Local Search (ILSeq) and exhaustive local search strategy with Iterative Local Search (ILSex) in Table 2. HyLS and ILSex achieved the top rankings, which were not significantly different from each other, and were both significantly better than ILSeq's and SEQ's.

Table 1: The best result of HyLS, MAENS and MASDC on DCARP instances.

Map	Ins	HyLS	MAENS [6]	MASDC [4]
S4-C	1	***10052***	22159.0	42285.0
	2	***10601***	22101.0	42878.0
	3	***10457***	21031.0	42094.0
Avr.Ranking		1	2	3
Friedman test		p-value=5.32e-32		
Nemenyi test		$CD = 0.3$		

Table 2: The median results of HyLS, ILSex, ILSeq and SEQ.

Map	Ins	HyLS	ILSex	ILSeq	SEQ
S4-C	1	***14760***	***14760***	14913	14913
	2	***14410***	14445	14418	14418
	3	***14142***	***14142***	14465	14465
Avr.Ranking		0.46	0.63	1.96	2.96
Friedman test		p-value=5.63e-39			
Nemenyi test		$CD = 0.43$			

4 CONCLUSION

In this paper, we focus on dynamic scenarios with small changes for the capacitated arc routing problem (DCARP). We propose a hybrid local search framework (HyLS) to reschedule the CARP solution within a short time budget for DCARP instances. We compared our proposed framework with existing methods in two sets of experiments, first evaluating a re-optimisation strategy and second analyzing the local search capability. Our results demonstrate that HyLS is very efficient in providing a good schedule within a very short time for the dynamic scenario with small changes compared with existing meta-heuristics and local search strategies.

ACKNOWLEDGMENTS

Hao Tong gratefully acknowledges the financial support from Honda Research Institute Europe (HRI-EU).

REFERENCES

[1] Ángel Corberán, Richard Eglese, Geir Hasle, Isaac Plana, and José María Sanchis. 2020. Arc routing problems: A review of the past, present, and future. *Networks* (June 2020).
[2] Philippe Lacomme, Christian Prins, and Wahiba Ramdane-Cherif. 2004. Competitive memetic algorithms for arc routing problems. *Annals of Operations Research* 131, 1-4 (2004), 159–185.
[3] Leon YO Li and Richard W Eglese. 1996. An interactive algorithm for vehicle routeing for winter—gritting. *Journal of the Operational Research Society* 47, 2 (1996), 217–228.
[4] Min Liu, Hemant Kumar Singh, and Tapabrata Ray. 2014. A memetic algorithm with a new split scheme for solving dynamic capacitated arc routing problems. In *2014 IEEE Congress on Evolutionary Computation (CEC)*. IEEE, 595–602.
[5] Yi Mei, Ke Tang, and Xin Yao. 2009. A global repair operator for capacitated arc routing problem. *IEEE Transactions on Systems, Man, and Cybernetics, Part B (Cybernetics)* 39, 3 (2009), 723–734.
[6] Ke Tang, Yi Mei, and Xin Yao. 2009. Memetic algorithm with extended neighborhood search for capacitated arc routing problems. *IEEE Transactions on Evolutionary Computation* 13, 5 (2009), 1151–1166.
[7] Hao Tong, Leandro L. Minku, Stefan Menzel, Bernhard Sendhoff, and Xin Yao. 2021. A Novel Generalised Meta-Heuristic Framework for Dynamic Capacitated Arc Routing Problems. arXiv:2104.06585